1.0	machine connection: drain connection hose, DN 22 hose fitted as odour trap in interior of machine					
1.1	drain (max. 700 mm above finished floor level), DN 50					440
2.0	Machine connection: fresh water supply, G 3/4"					
2.2	Soft cold water 10°C, DN 15, G 3/4 a max. 0,54 mmol/I CaCO₃ (max. 3°dH) Flow rate: 5 l/min Minimum flow pressure: 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar stopcock and fine screen ≤ 25 µm	····•		810 820 - 850	080	420
3.0	Machine connection: electrical connection cable 5G 2,5mm ²	00 00	b		L	285
<u>6.0</u> 6.1	electricity supply to the machine: 3N PE 400V ~ 50Hz nominal current / - capacity: 16,0 A / 6,9 kW Fuse protection: 16 A	80 1.1 2.2	600 80	10 - 40	50 550	3.0-
the p	osition of the connection piping can also be mirror-inverted!	3.1				
Mad	chine Equipment					
(A) E	ntry height	<u>}-</u> }-₩-				1.0 –′
(D) R	inse agent pipe and suction lance					
	etergent dosing unit with suction lance			600		
				Revision		

				Revision							
Ctra. de l'Hospit Cityparc Ronda 08940 Cornellà	Cityparc Ronda de Dait - Editició Atenas.				Reference DISHWASHER STANDARD DRAWING / PRT				Type UPSTER U 500 M2		
This drawing may not be neither passed to third parties for their information or copied or used for competitive purposes without our consent. All rights reserved. We reserve the right to make changes resulting from technical progress. This drawing was computer generated and is not subject to the checking and any release process; it is also not subject to change management. Please note:			TYPE: CROCKERY Drawing-No. S00089611				Order-No.				
	s document is only valid in conjunction with the conditions defined in Supplen eet "Important Information". These can be requested from the manufacturer o vnloaded from the Partnernet.			Scale 1:25	drawn: 13.08.2	2020	m-iplan	checked: 13.08.2020	m-iplan		
				PRT	E	N			Ccor	PYRIGHT by I	MEIKO

-A